



D2



Quick Connect Centers

The Camera & Sonde Test Port on the front of the Command Center will help you to trouble-shoot the camera/sonde which will save you time and money.

Remote Pouch

The remote is mounted on the side of the command module to allow easy access. Save time and increase productivity.



Mini Wheels

Push & Pull easily into any job site with no limitation while doing inspection.


Self-Leveling Camera

Camera size is 1.3" in diameter, Self-leveling camera head. Inspect from 2" to 12" pipes. Get into more inspections with just one camera, fewer repairs and fewer investments.



10.4" LCD Monitor

Inspect even the smallest details with high resolution pictures. Fold down like a laptop for easy to view and text-write.



Built-In Text writer

Simple and easy to use keyboard, it is water resistant for simple cleaning. Add onscreen text to the video.



Heavy-Duty Sewer Camera Inspection

Flexi-Guard Spring

Spring technology allows 90 degree bends and turns. Protects the camera and allow maximum flexibilities for an inspection.

TECHNICAL SPECIFICATIONS

- ✓ Internal battery (Nihm)
- ✓ Hi-resolution Color Camera (Inspect 2"-12" lines)
- ✓ 10.4" Hi-Resolution Color LCD
- ✓ Sealed weatherproof touchpad controls
- ✓ 512 Hz sonde with super flex design
- ✓ 8GB USB memory included
- ✓ DVR: One-touch, On-demand Remote Control USB recording
- ✓ .475" OD Premium fiberglass push rod
- ✓ On-Screen digital distance counter
- ✓ 1.3" OD Self-Leveling Camera head



- ✓ MODULAR CAMERA – Quick Change
- ✓ CARTRIDGE STYLE – Repair Quickly
- ✓ ENCAPSULATED– Cost Effective
- ✓ 1.3" DIAMETER – More Inspection
- ✓ GORILLA GLASS – Water Resistant
- ✓ POWER LED – Shines Bright